

UTILITY PATENT APPLICATION TRANSMITTAL (Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
00USFP543-HS

Total Pages in this Submission

TO THE ASSISTANT COMMISSIONER FOR PATENTSBox Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

MOBILE WIRELESS COMMUNICATION SYSTEM CARRYING OUT COMMUNICATION OF A PORTABLE TERMINAL, AN INFORMATION SOURCE SERVER APPARATUS AND A WIRELESS COMMUNICATION GATEWAY SERVER APPARATUS

and invented by:

Hidehiro Matsumoto

If a CONTINUATION APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Which is a:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No.: _____

Enclosed are:

Application Elements

1. ☒ Filing fee as calculated and transmitted as described below
2. ☒ Specification having 55 pages and including the following:
 - a. ☒ Descriptive Title of the Invention
 - b. ☐ Cross References to Related Applications (if applicable)
 - c. ☐ Statement Regarding Federally-sponsored Research/Development (if applicable)
 - d. ☐ Reference to Microfiche Appendix (if applicable)
 - e. ☒ Background of the Invention
 - f. ☒ Brief Summary of the Invention
 - g. ☒ Brief Description of the Drawings (if drawings filed)
 - h. ☒ Detailed Description
 - i. ☒ Claim(s) as Classified Below
 - j. ☒ Abstract of the Disclosure

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
00USFP543-HS

Total Pages in this Submission

Application Elements (Continued)

3. ☒ Drawing(s) *(when necessary as prescribed by 35 USC 113)*
- a. ☒ Formal Number of Sheets 8 (Figs. 1-9)
- b. ☐ Informal Number of Sheets _____
4. ☒ Oath or Declaration
- a. ☒ Newly executed *(original or copy)* ☐ Unexecuted
- b. ☐ Copy from a prior application (37 CFR 1.63(d)) *(for continuation/divisional application only)*
- c. ☒ With Power of Attorney ☐ Without Power of Attorney
- d. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named in the prior application,
see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation By Reference *(usable if Box 4b is checked)*
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied
under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby
incorporated by reference therein.
6. ☐ Computer Program in Microfiche *(Appendix)*
7. ☐ Nucleotide and/or Amino Acid Sequence Submission *(if applicable, all must be included)*
- a. ☐ Paper Copy
- b. ☐ Computer Readable Copy *(identical to computer copy)*
- c. ☐ Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. ☒ Assignment Papers *(cover sheet & document(s))*
9. ☐ 37 CFR 3.73(B) Statement *(when there is an assignee)*
10. ☐ English Translation Document *(if applicable)*
11. ☒ Information Disclosure Statement/PTO-1449 ☒ Copies of IDS Citations
12. ☐ Preliminary Amendment
13. ☒ Acknowledgment postcard
14. ☐ Certificate of Mailing
- ☐ First Class ☐ Express Mail *(Specify Label No.):* _____

**UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
00USFP543-HS

Total Pages in this Submission

Accompanying Application Parts (Continued)

15. ☒ Certified Copy of Priority Document(s) *(if foreign priority is claimed)*

16. ☐ Additional Enclosures *(please identify below):*

Request That Application Not Be Published Pursuant To 35 U.S.C. 122(b)(2)

17. ☐ Pursuant to 35 U.S.C. 122(b)(2), Applicant hereby requests that this patent application not be published pursuant to 35 U.S.C. 122(b)(1). Applicant hereby certifies that the invention disclosed in this application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication of applications 18 months after filing of the application.

Warning

An applicant who makes a request not to publish, but who subsequently files in a foreign country or under a multilateral international agreement specified in 35 U.S.C. 122(b)(2)(B)(i), must notify the Director of such filing not later than 45 days after the date of the filing of such foreign or international application. A failure of the applicant to provide such notice within the prescribed period shall result in the application being regarded as abandoned, unless it is shown to the satisfaction of the Director that the delay in submitting the notice was unintentional.

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
00USFP543-HS


Total Pages in this Submission

Fee Calculation and Transmittal

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	26	- 20 =	6	x \$18.00	\$108.00
Indep. Claims	5	- 3 =	2	x \$80.00	\$160.00
Multiple Dependent Claims (check if applicable) <input type="checkbox"/>					\$0.00
BASIC FEE					\$710.00
OTHER FEE (specify purpose) <u>Assignment Recordation</u>					\$40.00
TOTAL FILING FEE					\$1,018.00

- ☒ A check in the amount of \$1,018.00 to cover the filing fee is enclosed.
- ☒ The Commissioner is hereby authorized to charge and credit Deposit Account No. 50-0481 as described below. A duplicate copy of this sheet is enclosed.
- ☐ Charge the amount of _____ as filing fee.
- ☒ Credit any overpayment.
- ☒ Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.
- ☐ Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).


Signature

Sean M. McGinn
Registration No. 34,386
Customer No. 21254

Dated: October 25, 2000

cc:

McGINN & GIBB, PLLC
A PROFESSIONAL LIMITED LIABILITY COMPANY
PATENTS, TRADEMARKS, COPYRIGHTS, AND INTELLECTUAL PROPERTY LAW
1701 CLARENDON BOULEVARD, SUITE 100
ARLINGTON, VIRGINIA 22209
TELEPHONE (703) 294-6699
FACSIMILE (703) 294-6696

**APPLICATION
FOR
UNITED STATES
LETTERS PATENT**

APPLICANT: Hidehiro Matsumoto

FOR: MOBILE WIRELESS
COMMUNICATION SYSTEM
CARRYING OUT COMMUNICATION
OF A PORTABLE TERMINAL, AN
INFORMATION SOURCE SERVER
APPARATUS AND A WIRELESS
COMMUNICATION GATEWAY
SERVER APPARATUS

DOCKET NO.: 00USFP543-HS

MOBILE WIRELESS COMMUNICATION SYSTEM CARRYING OUT
COMMUNICATION OF A PORTABLE TERMINAL,
AN INFORMATION SOURCE SERVER APPARATUS AND
A WIRELESS COMMUNICATION GATEWAY SERVER APPARATUS

5

Background of the Invention

1. Field of the Invention

The present invention relates to a mobile communication system in which a portable terminal accesses information source server apparatus existing on a network through a wireless communication line. More particularly, the present invention relates to a mobile communication system for reducing a time required for a portable terminal to access information source server apparatus, a wireless communication gateway server apparatus, a position information calculation system, a method for reducing a connection time in the system, and a record medium for recording therein a connection time reduction program.

2. Description of the Related Art

Recently, a function has been proposed in which a portable terminal accesses information source server apparatus existing on a network (especially, the Internet) and obtains information from the network.

Fig. 1 shows an example of a configuration of a system in which this portable terminal accesses the information source server apparatus existing on the network.

As shown in Fig. 1, a dedicated server apparatus

referred to as a wireless communication gateway server apparatus 24 is installed at an access point to a network, in order to access the network from a portable terminal 20.

5 This wireless communication gateway server apparatus 24 and the portable terminal 20 are connected to each other through a wireless communication line. In this wireless communication line, a communication is done, for example, by using a communication protocol referred to as WAP (Wireless Application Protocol) optimized for
10 the characteristic of a wireless communication and a portable terminal. Also, a communication between the wireless communication gateway server apparatus 24 and the information source server apparatus 26 on the network is
15 done in accordance with a standard protocol for the network [for example, in a case of the Internet, an Internet standard protocol {for example, HTTP (Hyper-Text Transfer Protocol) and TCP (Transmission Control Protocol)}}].

 The wireless communication gateway server apparatus
20 24 has an executing device for executing: a process for carrying out a protocol conversion between a communication protocol on a wireless communication line and a standard protocol on a network on which the information source server apparatus 26 exists; a data conversion process, for
25 example, a process in which if information stored in the information source server apparatus 26 on the network is a document written under a HTML (Hypertext Markup Language)

type, this document in the HTML type is converted into a document in a WML (Wireless Application Language) type used in the WAP; and a process in which if a document stored in information source server apparatus S on a network is, for example, a WML document in a text type, it is converted into a binary type, and then a data is compressed.

Also, the wireless communication gateway server apparatus 24 has a buffer memory emulator 25, as shown in Fig. 1. In this apparatus, in order to solve the unstableness in a communication condition caused by a bandwidth and a delay amount in a wireless data communication network and an intermission in a wireless communication line, this buffer memory emulator 25 transiently stores therein a data sent by the information source server apparatus. The data for the buffer memory emulator 25 means, for example a memory size and a consumed size of the buffer memory 2. The consumed size means, for example a size used for storing the information from the information source server apparatus 7. Then, it monitors a condition of a buffer memory at a portable terminal, carries out a control so that the data does not overflow the buffer memory, and sends the data to the portable terminal.

Moreover, the portable terminal can be freely moved. Thus, it is necessary that a current area in which the portable terminal itself presently exists is always reported to a system side (a switching station) (this

function is referred to as a position register).

The method for registering a position will be described below. An area number indicative of a position register area is always reported by a base station (not shown). The portable terminal 20 always compares an area number stored in the self-terminal with the reported area number, and sends a position register signal through the base station to a switching apparatus if those area numbers do not coincide with each other. The switching apparatus converts the position register signal sent by the portable terminal into a position information on which a line setting can be performed, and then registers it in a position information database 23. Thus, the system side can recognize a new position of the portable terminal 20. Hence, for example, if this portable terminal is accessed, a switching apparatus 22 can send a number information of the portable terminal to the position information database 23 and thereby connect a call to a desirable portable terminal, in accordance with information indicative of a position in which the portable terminal exists, from the number information fed back from the position information database 23.

The method for the portable terminal 20 to access the information source server apparatus 26 on the network will be described below, in the mobile communication system having the above-mentioned configuration. At first, when a power source of the portable terminal 20 is turned on,

a position information of the portable terminal 20 is registered in the position information database 23 through the nearest base station. Next, since this portable terminal 20 issues a call to a telephone number of an access point which is registered in advance, a call is established between it and a wireless communication gateway server apparatus 24 having the access point.

An access request to the information source server apparatus 26 from the portable terminal 20 is reported to the wireless communication gateway server apparatus in a suitable wireless data protocol, for example, in the HTTP or WAP. So, it is possible to select and specify information source server apparatus by using URL (Uniform Resource Locator).

However, in the above-mentioned conventional mobile communication system, when the portable terminal accesses the information source server apparatus existing on the network, it must telephone a registered telephone number of only one access point assigned to the portable terminal, and then access the network through this access point. Thus, if a congestion is induced in this access point, a user of the portable terminal must again telephone the access point after a while. Also, it is impossible to obtain an insurance that the user can access the network after an elapse of a predetermined time.

If the demand from the users becomes equal to or greater than the number of terminals (the congestion state)

that can be accommodated in the access point used when the wireless communication gateway server apparatus and the portable terminal communicate with each other, it is necessary to separately install the access point used by the portable terminal, in order to reduce a connection wait time of the user. At this time, a process for initializing a buffer memory within the wireless communication gateway server apparatus just before must be initialized. Hence, the user must wait by a time necessary for the initialization and a time for the connection to another access point.

If because of the movement of the portable terminal or the occurrence of the congestion in the access point disables the establishment of the connection to the wireless communication gateway server apparatus used just before, the connection to the wireless communication gateway server apparatus is done through another access point. However, even in this case, it is necessary to initialize the process for monitoring the buffer memory. In this case, the user must further wait by the switching time in the wireless communication gateway server apparatuses, in addition to the above-mentioned delay time. The fact that the user must wait not only results in a waste of a communication line resource, but also imposes an economic burden on the user when a communication fee or a service accounting based on a time is charged.

The techniques with regard to the switched capacitor

type digital-analog converter are disclosed in Japanese Laid Open Patent Application (JP-A-H7-264662), Japanese Laid Open Patent Application (JP-A-H9-130861), Japanese Laid Open Patent Application (JP-A-H10-210533), Japanese Laid Open Patent Application (JP-A-H10-327454) and Japanese Laid Open Patent Application (JP-A-H11-83976).

The present invention is accomplished in view of the above mentioned problems.

10

Summary of the invention

The present invention provides a mobile communication system which can reduce a time required for a portable terminal to access information source server apparatus existing on a network, a wireless communication gateway server apparatus, a position information calculation system, a method for reducing a connection time in the system, and a record medium for recording therein a connection time reduction program.

The mobile wireless communication system according to the invention is provided with information source server apparatus(7), a portable terminal(1), a plurality of wireless communication gateway server apparatuses(5A,5B), a switching apparatus(3) and a wireless telephony server(8). The information source server apparatus stores information. The portable terminal carrying out a communication with the information source server apparatus and having a buffer memory(2) which stores the

information transmitted from the information source server apparatus. The plurality of wireless communication gateway server apparatuses, wherein a specific one of the plurality of wireless communication gateway server apparatuses which is determined based on an informed position of the portable terminal, has a buffer memory emulator which stores specification data which represents a specification of the buffer memory and transmitters the information from the information source server apparatus to the portable terminal based on the specification data. The switching apparatus setting a specific one connection between the portable terminal and a specific one wireless communication gateway server apparatus or another connection between the portable terminal and another wireless communication gateway server apparatus, which is used when the communication between the portable terminal and the specific one wireless communication gateway server apparatus congests. The wireless telephony server apparatus informing the position of the portable terminal to the plurality of wireless communication gateway server apparatuses.

In another mobile wireless communication system according to the invention, the specific one wireless communication gateway server apparatus(5A) requests the switching apparatus to change a connection from the specific one connection to the other connection based on the informed position.

In another mobile wireless communication system according to the invention, the specific one wireless communication gateway server apparatus (5A) decides the other wireless communication gateway server apparatus (5B) so that a new connecting destination of a connection between the one connection and the other connection is determined.

In another mobile wireless communication system according to the invention, the specific one wireless communication gateway server apparatus (5A) informs to the other wireless communication gateway server apparatus the specification data which is read from the buffer memory emulator. Furthermore, the other wireless communication gateway server apparatus (5A) stores the read specification data in the buffer memory emulator thereof and transfers the information from the information source server apparatus to the portable terminal based on the read specification data.

Another mobile wireless communication system is provided with a network which is connected to the specific one wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus. In the above mobile wireless communication system, the specific one wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the

wireless telephony server apparatus communicate through the network.

Another mobile wireless communication system is provided with an internet network which is connected to the specific one wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus. In the above mobile wireless communication system, the specific one wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the internet network.

Another mobile wireless communication system is provided with a satellite network which is connected to the specific one wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus. In the above mobile wireless communication system, the specific one wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the satellite network.

The mobile wireless communication system according to the invention is provided with an information source server apparatus (7), a portable terminal (1), a wireless

communication gateway server apparatus (5A), a switching apparatus (3), a wireless telephony server apparatus (8). The information source server apparatus stores information. The portable terminal carries out a communication with the information source server apparatus and has a buffer memory which stores the information transmitted from the information source server apparatus. The wireless communication gateway server apparatus has a buffer memory emulator which stores specification data which represents a specification of the buffer memory. Furthermore, the wireless communication gateway server apparatus has a plurality of access points (APa, APb), specific one of which is determined based on an informed position of the portable terminal. Furthermore, the wireless communication gateway server apparatus transfers the information from the information source server apparatus to the portable terminal based on the specification data. The switching apparatus sets specific one connection between the portable terminal and specific one access point or another connection between the portable terminal and another access point, which is used when the one access point congests. The wireless telephony server apparatus informs the position of the portable terminal to the wireless communication gateway server apparatus.

In another mobile wireless communication system, the wireless communication gateway server apparatus requests the switching apparatus to change a connection from the

specific one connection to the other connection based on the informed position.

In another mobile wireless communication system the wireless communication gateway server apparatus refers the
5 specification data in the buffer memory emulator to access the portable terminal through the other access point.

Another mobile wireless communication system is provided with a network which is connected to the wireless communication gateway server apparatus, the switching
10 apparatus and the wireless telephony server apparatus. In the above mobile wireless communication system, the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the network.

15 Another mobile wireless communication system is provided with an internet network which is connected to the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus. In the above mobile wireless communication
20 system the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the internet network.

Another mobile wireless communication system is provided with a satellite network which is connected to the wireless
25 communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus. In the above mobile wireless communication system, the

wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the satellite network.

The method for mobile wireless communication system
5 is provided with a storing, a changing and transferring.
In the storing, a specification data which represents a specification of a buffer memory of a portable terminal is stored in a buffer memory emulator of specific one
10 wireless communication gateway server apparatus when the portable terminal is connected to the specific one wireless communication gateway server apparatus. In the changing, specific one connection between the portable terminal and the specific one wireless communication gateway server apparatus is changed to another connection between the
15 portable terminal and one of another wireless communication gateway server apparatus, which is used when the specific one wireless communication gateway server apparatus has a congestion. In the transferring, the specification data from the specific one wireless
20 communication gateway server apparatus is transferred to the another wireless communication gateway server apparatus when the other connection is set.

Another method for mobile wireless communication system is provided with a informing and a requesting. In
25 the informing, a position of the portable terminal is informed from a wireless telephony server apparatus to the specific one wireless communication gateway server

apparatus. In the requesting, a change from a specific one connection to the other connection is requested to a switching apparatus which sets a connection for the portable terminal based on the informed position.

5 Another method for mobile wireless communication system is provided with a communicating. In the communicating, the specific one wireless communication gateway server apparatus, another wireless communication gateway server apparatus, the another the switching
10 apparatus and the wireless telephony server apparatus communicate are communicated through a network.

In another method for mobile wireless communication system, the specific one wireless communication gateway server apparatus, another wireless communication gateway
15 server apparatus, the switching apparatus and the wireless telephony server apparatus are communicated through an internet network.

In another method for mobile wireless communication system, the specific one wireless
20 communication gateway server apparatus, another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus are communicated through a satellite network.

In another method for mobile wireless communication
25 system, specific one connection between the portable terminal and one access point of a wireless communication gateway server apparatus is changed to another connection

between the portable terminal and another access point of the wireless communication gateway server apparatus, which is used when the wireless communication gateway server apparatus has a congestion.

5 The above method of mobile wireless communication system is provided with informing and requesting. In the above informing, a position of the portable terminal from a wireless telephony server apparatus is informed to the wireless communication gateway server apparatus. In the
10 requesting, a change from a specific one connection to the other connection is requested to a switching apparatus which sets a connection for the portable terminal based on the informed position.

 In the above method for mobile wireless
15 communication system, the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus are communicated through a network.

 In the above method for mobile wireless
20 communication system, the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus are communicated through an internet network.

 In the above method for mobile wireless
25 communication system, the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus are communicated through a

satellite network.

The wireless communication gateway server apparatus according to the invention is provided with a buffer memory emulator. The buffer memory emulator stores a
5 specification data which represents a specification of a buffer memory of a portable terminal. In the above wireless communication gateway server apparatus, specific one connection with the portable terminal is changed to another connection between the portable terminal and
10 another wireless communication gateway server apparatus, which is used when a congestion of the specific one connection is happened. In the above wireless communication gateway server apparatus the specification data in the buffer memory is transferred to the another
15 wireless communication gateway server apparatus.

In the above wireless communication gateway server apparatus, a change is requested to the switching apparatus which sets a connection for the portable terminal from the specific one connection to the other connection based on
20 a position data of the portable terminal.

The above wireless communication gateway server apparatus is provided with a plurality of access points, wherein a specific one of the plurality of access points which is determined based on an informed position of the
25 portable terminal.

In the above wireless communication gateway server apparatus, a change is requested to the switching apparatus

which sets a connection for the portable terminal from a specific one connection of the specific one access point to another connection of another access point based on the position of the portable terminal.

5

Brief Description of the Drawings

Fig. 1 is a block diagram showing a configuration of a conventional mobile wireless communication system;

Fig. 2 is a block diagram showing a configuration
10 of an embodiment according to the present invention;

Fig. 3 is a view showing a management table;

Fig. 4 is a view showing a configuration of an embodiment;

Fig. 5 is a view describing a communication example
15 when it is connected to an access point managed by the same wireless communication gateway server apparatus;

Fig. 6 is a view describing a communication example when it is connected to an access point managed by the same wireless communication gateway server apparatus;

20 Fig. 7 is a view describing a communication example when it is connected to an access point managed by a different wireless communication gateway server apparatus;

Fig. 8 is a view describing a communication example
25 when it is connected to an access point managed by a different wireless communication gateway server apparatus; and

Fig. 9 is a block diagram showing a configuration of another embodiment.

Description of the Preferred Embodiments

5 The embodiments with regard to a mobile communication system, a wireless communication gateway server apparatus, a position information calculation system, a method for reducing a connection time in the system and a record medium for recording therein a
10 connection time reduction program, according to the present invention, will be described below in detail with reference to the attached drawings.

Fig. 2 shows the configuration of the embodiment according to the present invention. The embodiment
15 according to the record medium for recording therein the connection time reduction program can be attained by storing a record medium, which records therein a control program, in the following respective devices. As this record medium, a semiconductor memory, an optical disc,
20 a magneto-optic disc, a magnetic record medium and the like can be used.

As shown in Fig. 2, this embodiment is provided with:
a portable terminal 1 which uses a wireless communication line; a switching apparatus 3 for carrying out the
25 desirable connection, based on a telephone number of a destination included in a call connection information from the portable terminal 1 and the like; a position

information database 4 for recording therein a current position of the portable terminal 1; a wireless communication gateway server apparatus 5 which exists on a network and communicates through the wireless

5 communication line with the portable terminal 1; information source server apparatus 7 that exists on the network on which the wireless communication gateway server apparatus 5 exists; and a wireless telephony server apparatus 8 that exists on the network and can obtain a
10 position information of the portable terminal 1 from the position information database 4. In this embodiment, between a plurality of wireless communication gateway server apparatuses 5, each of the wireless communication gateway server apparatuses 5, the information source
15 server apparatus 7 and the wireless telephony server apparatus 8 are connected through the Internet to each other, and they can send and receive information to and from each other. However, this network is not limited to the Internet.

20 The portable terminal 1 is constituted by a terminal which carries out a communication by using a wireless communication line such as PHS (Personal Handy-phone System), a portable telephone and the like. Also, the portable terminal 1 has a buffer memory 2 for storing
25 therein information transferred by the information source server apparatus 7 and the like. The information means, for example HTML (Hypertext Markup Language) data for a web

site.

In order that a system side (a switching apparatus side) recognizes a position of the movable portable terminal 1, the position information database 4 captures
5 an identifier and a position of a base station belonging to a cell on a control route 10 in the wireless communication line, in a case of a cell type, and always registers therein the newest position of the portable terminal 1. Actually, a base station (not shown) always transmits a position
10 information of the base station within the cell. The portable terminal 1 stores therein the position information transmitted by the nearest base station. When because of a movement of a user, the portable terminal 1 is moved from a cell managed by the base station to another
15 cell, if a position information received at that location is different from the stored position information, the stored position information is changed into the newly received position information, and a register request with regard to the change into a new position is performed on
20 the base station. This position information is registered in the position information database 4 through a common line signal network from the switching apparatus 3.

The switching apparatus 3 switches a connection to
25 a line for a destination indicated by a telephone number, in accordance with the telephone number included in the connection request from a wireless communication gateway

server apparatus, or a portable terminal.

The position information database 4 has a function of searching the stored position information of the portable terminal, in accordance with an individual number
5 of a portable terminal transferred by the wireless telephony server apparatus 8, and finding out a cell ID indicative of a cell to which the portable terminal currently belongs, and then transmitting to a request source. Especially, in a case of a PDC (Personal Digital
10 Cellular phone) type, this position information database 4 is referred to as HLR (Home Location Register).

Fig. 3 shows an example of a management table managed by the position information database. As shown in Fig. 3, the management table managed by the position information
15 database records therein a terminal number of each portable terminal, a cell ID indicative of a position of a base station to which the portable terminal currently belongs, an accounting meter for calculating a usage fee for each portable terminal and the like.

20 The wireless communication gateway server apparatus 5 has a buffer memory emulator 6. This buffer memory emulator 6, in order to solve the unstableness of a communication condition caused by a network, a band width and a delay amount of the wireless communication line
25 network, and an intermission of the wireless communication line, transiently accumulates therein a data transmitted by the information source server apparatus 7, and monitors

a condition of the buffer memory 2 which is mounted in the portable terminal 1 and stores therein the data, and carries out a control so that the data does not overflow the buffer memory 2, and then sends the data to the portable
5 terminal 1.

Also, the wireless communication gateway server apparatus 5 has the following functions in addition to the above-mentioned function. For example, it has: a function in which if the WAP is used for a communication
10 protocol in the portable terminal 1 using the wireless communication line and then a standard protocol in the Internet is used for a communication protocol in the network, a protocol conversion is done between the communication protocol in the WAP and the standard protocol
15 in the network; a data conversion function, for example, a function in which if a document in the HTML type is stored in the information source server apparatus 7 on the network, the document in the HTML type is converted into a document in the WML (Wireless Markup Language) type used in the WAP,
20 a function in which if a document in the text type is stored in the information source server apparatus 7 on the network, the document in the text type is converted into the binary type, and the data is compressed; and the like.

The information source server apparatus 7, which
25 exists on the network, transmits the stored information, in accordance with a request from the portable terminal 1.

The wireless telephony server apparatus 8 is a kind of information source server apparatus for providing information. So, it can use the position information database 4 to thereby obtain information with regard to
5 the portable terminal 1 registered in the position information database 4.

A first object of a first embodiment having the above-mentioned configuration lies in a reduction of a time necessary for a connection process to the Internet of users
10 by establishing another access point if the demand from the users becomes equal to or greater than the number of terminals that can be accommodated in an access point (a congestion state), in the access point serving as a connection point to the Internet, when the portable
15 terminal 1 accesses information source server apparatus 7 connected to the Internet.

A second object of the embodiment having the above-mentioned configuration lies in a reduction of a time necessary for a re-connection by preparing in advance the
20 condition of a buffer memory before a disconnection with regard to the portable terminal 1, in the wireless communication gateway server apparatus 5, on the basis of a connected position, if a congestion is induced in an access point connected just before, when the portable
25 terminal 1 again accesses information source server apparatus, at a time of the disconnection of the wireless communication line or after a user ends a communication.

In order to attain the first object, the wireless communication gateway server apparatus 5, if a congestion is induced in an access point managed by it, instructs the switching apparatus 3 to carry out a connection to another access point. Then, the switching apparatus 3 carries out a process for carrying out a connection to the instructed access point, if the portable terminal 1 issues a call to the access point in which the congestion is induced.

Accordingly, it is possible to solve the trouble induced when the conventional portable terminal accesses the network, and the trouble in which since the number of access points is one, if the congestion is induced in the access point, it must issue a call to the access point again after a while or the connection can not be established even if it tries to issue a large number of calls to the access point.

In order to attain the second object, the wireless communication gateway server apparatus 5 for transiently storing in a buffer memory (not shown) information transferred by the information source server apparatus 7 and a position and an attribute value of a portable terminal connected to an access point, stores therein the above-mentioned information initialized at the stage when the communication with the portable terminal is disconnected, without the initialization for a certain period. Also, the wireless communication gateway server apparatus 5 recognizes the histories with regard to an

individual number of a portable terminal that is connected to the wireless telephony server apparatus 8 for a certain period and also connected to an access point which it belongs, and information about a cell ID in which the portable terminal exists. This can be attained by the following operations. That is, the wireless communication gateway server apparatus 5 transfers the kind report sent by the portable terminal to the wireless telephony server apparatus 8 for each certain cycle. The wireless telephony server apparatus 8 transfers the sent kind report to the position information database 4. Then, it obtains a cell ID indicative of a cell to which the portable terminal 1 currently belongs, and then transfers to the wireless communication gateway server apparatus 5. By the way, the kind report transferred to the wireless communication gateway server apparatus 5 from the portable terminal 1 at the time of the connection to the access point includes the terminal attribute indicative of an individual number of the portable terminal, an amount of the buffer memory, a size of a display region, a processing ability and the like.

Thus, after the wireless communication line is disconnected or after the user of the portable terminal 1 ends the communication, when the portable terminal again accesses the information source server apparatus 7, if a congestion is induced in an access point and thereby the portable terminal is connected to another access point,

since the wireless communication gateway server apparatus
5 stores therein the information transferred by the
information source server apparatus 7 and the position and
the attribute value of the portable terminal connected to
5 the access point, it is possible to continue the process
in the buffer memory emulator 6 and also possible to
continue the services such as the accounting process and
the like.

Even if the movement of the user of the portable
10 terminal 1 causes the portable terminal 1 to be connected
to another access point different from an access point
connected just before and further the access point is a
wireless communication gateway server apparatus different
from a wireless communication gateway server apparatus
15 carrying out a process just before, the wireless
communication gateway server apparatus sends a kind report
of the portable terminal to the wireless telephony server
apparatus 8. The wireless telephony server apparatus 8
obtains the position information before and after the
20 connection to the portable terminal from the position
information database 4, and compares them with each other,
and then finds out the wireless communication gateway
server apparatus used just before. Thus, various
parameters for the buffer memory emulator can be obtained
25 from the wireless communication gateway server apparatus
connected just before. Hence, it is possible to reduce
the time necessary for the connection process and also

possible to continue the services such as the accounting process and the like. By the way, the various parameters for the buffer memory emulator 6 include a parameter indicative of a condition of the buffer memory, a parameter
5 indicative of an attribute of a portable terminal, a parameter indicative of a position information of the portable terminal and the like.

A series of flows in the above-mentioned processes according to this embodiment will be described below in
10 detail.

As shown in Fig. 2, the portable terminal 1 captures the identifier and the position of the base station belonging to the cell on the control route 10 in the wireless communication line, in the case of the cell type, and always
15 registers the newest position in the position information database 4. Also, the portable terminal 1 is connected to the wireless communication gateway server apparatus 5 through the wireless communication network up to the access point. The connection to the wireless communication
20 gateway server apparatus 5 from the portable terminal 1 is established by issuing a call to a telephone number of the access point assigned to the portable terminal. After that, the communication route to the wireless communication gateway server apparatus is established
25 through a proper wireless communication protocol, for example, the HTTP or the WAP, as shown in Fig. 4.

The portable terminal 1, when it is connected to the

wireless communication gateway server apparatus 5,
transfers the kind report to identify the portable terminal,
to the wireless communication gateway server apparatus 5.
This kind report includes the terminal attribute, such as
5 the individual number of the portable terminal, the amount
of the buffer memory, the size of the display region, the
processing ability and the like.

The wireless communication gateway server apparatus
5 validates the legality of the portable terminal, in
10 accordance with the kind report obtained from the portable
terminal 1. In this process, the wireless communication
gateway server apparatus firstly transfers the kind report
sent by the portable terminal to the wireless telephony
server apparatus. The wireless telephony server
15 apparatus transfers the individual number of the portable
terminal from the transferred kind report to the position
information database, and obtains the kind report of the
portable terminal registered in the position information
database. Then, the legality of the portable terminal is
20 validated by comparing those kind reports with each other.

The portable terminal can select and specify
information source server 7 by specifying URL (Uniform
Resource Locator) of information source server apparatus
7 on a network from which a user desires to obtain
25 information.

The wireless communication gateway server apparatus
5, when the legality of the portable terminal is proved,

converts the wireless communication protocol used in the communication with the portable terminal into a standard protocol in the Internet, for example, a communication protocol based on the HTTP or the TCP, and then communicates
5 with the information source server apparatus 7 requested by the portable terminal 1. Thus, the wireless communication gateway server apparatus 5 can obtain the information stored in the information source server apparatus 7. The wireless communication gateway server
10 apparatus 5 stores the information sent by the information source server apparatus 7 in a buffer memory (not shown).

At this time, in the wireless communication gateway server apparatus 5, in order to monitor the overflow of the buffer memory 2 on the terminal side, the buffer memory
15 emulator 6 calculates a consumptive amount of the buffer memory based on the number of data packets received by the portable terminal 1 and the number of already processed packets.

Here, let us suppose that a congestion is induced
20 in the access point, when the portable terminal again accesses the information source server apparatus 7, after the wireless communication line is disconnected or after a user ends the communication. The wireless telephony server apparatus 8, when the congestion is induced in the
25 access point to which it belongs, instructs the switching apparatus 3 to carry out the connection to another access point. Then, the switching apparatus 3, when the portable

terminal 1 issues a call to the access point in which the congestion is induced, carries out a process for switching a connection to the instructed access point.

At this time, when the portable terminal issues the
5 call, the connection to the access point is done. However, there are the case that it is connected to an access point belonging to the same wireless communication gateway server apparatus, as shown in Fig. 5 or 6, and the case that it is connected to an access point belonging to a
10 different wireless communication gateway server apparatus because of the movement of the portable terminal, as shown in Fig. 7 or 8.

At first, with reference to Figs. 4 and 5, a communication example is described in which a congestion
15 is induced in an illustrated access point A, and it is connected to an access point B belonging to the same wireless communication gateway server apparatus 5A at a time of a re-connection. For the purpose of simple explanation, it is assumed that the access points A, B
20 belong to the same cell.

The wireless communication gateway server apparatus 5A, when it is connected to the portable terminal 1, compares a kind report reported by the portable terminal 1 with a kind report of the portable terminal 1, which is
25 stored in advance in the buffer memory. Then, it is checked whether or not the portable terminal 1 requesting the connection is the same portable terminal. If it is

checked that the reported kind report is identical to the kind report stored in the buffer memory, the buffer memory emulator 6 does not carry out the process for initializing information with regard to the portable terminal.

5 Thus, it is possible to reduce the time necessary for the process for connecting the portable terminal, and also possible to continue the services such as the accounting process and the like. Hence, when the communication fee or the service accounting based on the
10 time is charged, it is possible to reduce the economic burden on the user.

 In order to validate whether or not the legality of the portable terminal and the accounting process based on the provision service are started, the kind report of the
15 portable terminal 1 at the time of the re-connection is sent through the Internet to the wireless telephony server apparatus 8. The wireless telephony server apparatus 8 sends the individual number of the portable terminal 1 included in the received kind report to the position
20 information database 4, and obtains an attribute value registered in the position information database 4. This attribute value is compared with the attribute value obtained from the wireless communication gateway server apparatus 5A to thereby check the legality of the portable
25 terminal. Moreover, an accounting condition of the portable terminal 1 is checked by obtaining an accounting condition registered in the position information database

4. After the check, the wireless telephony server apparatus 8 sends a check report to the wireless communication gateway server apparatus 5 sending the kind report. Accordingly, the process of the buffer memory emulator 6 is continued.

By the way, the wireless communication gateway server apparatus 5A checks a terminal which is connected to the wireless telephony server apparatus 8 at a certain cycle and connected to the access point that it belongs.

10 After the check, the wireless telephony server apparatus 8 sends a check report to the wireless communication gateway server apparatus 5A sending the kind report. Accordingly, the process of the buffer memory emulator 6 is continued.

15 Usually, the time necessary for the initializing process is longer than that of the checking process, because of the re-establishment of the configuration of the buffer memory. Thus, the connection time in this method is shorter than that of the conventional technique.
20 Hence, the continuation of the process in the buffer memory emulator enables the services, such as the accounting process and the like, to be continued.

A case will be described below in which the portable terminal 1 is moved from a cell A to another cell B and
25 it is connected to an access point C belonging to a different wireless communication gateway server apparatus 5B.

When the portable terminal 1 is connected to the same

wireless communication gateway server apparatus at the time of the re-connection to the mobile communication system, a kind report of the portable terminal just before coincides with a kind report stored in the buffer memory emulator. However, if it is connected to a different wireless communication gateway server apparatus, the kind report reported by the portable terminal 1 does not coincide with a kind report of the portable terminal that is stored in the wireless communication gateway server apparatus.

So, the wireless communication gateway server apparatus sends the reported kind report of the portable terminal through the Internet to the wireless telephony server apparatus 8.

The wireless telephony server apparatus 8 accesses the position information database 4, and finds out a URL of the wireless communication gateway server apparatus 5A to which the portable terminal 1 requesting the connection is connected just before. Then, the found out URL of the wireless communication gateway server apparatus 5A is transferred to the wireless communication gateway server apparatus 5B sending the kind report.

The wireless communication gateway server apparatus 5B to which the URL is reported requests various parameters held by the buffer memory emulator, to the wireless communication gateway server apparatus 5B of the reported URL. The requested wireless communication gateway server

apparatus 5A sends the various parameters held by the buffer memory emulator, to the wireless communication gateway server apparatus 5A of the request source. The wireless communication gateway server apparatus 5B

5 receiving the report of the various parameters with regard to the portable terminal 1 copies the received various parameters of the portable terminal 1 to the buffer memory emulator.

At this time, the portable terminal 1 is acquired
10 by the wireless telephony server apparatus 8, and the wireless telephony server apparatus 8 is cyclically connected to the wireless communication gateway server apparatuses 5A, 5B. Thus, it is possible to judge the terminal connected to the access point under the control
15 of each wireless communication gateway server apparatus. Hence, as compared with the case that the portable terminal moved to another cell is initialized by the wireless communication gateway server apparatus, in this method, the process in the buffer memory emulator can be continued

apparatus 5A sends the various parameters held by the buffer memory emulator, to the wireless communication gateway server apparatus 5A of the request source. The wireless communication gateway server apparatus 5B

5 receiving the report of the various parameters with regard to the portable terminal 1 copies the received various parameters of the portable terminal 1 to the buffer memory emulator.

At this time, the portable terminal 1 is acquired

In this case, as shown in Fig. 9, receivers for receiving an electric wave from a satellite 13 are mounted on a portable terminal side 1 and a ground station 12. The GPS ground station 12 can receive all electric waves from all satellites. However, a GPS receiver 11 of a portable terminal can not receive the electric waves from all the satellites. So, a satellite from which the GPS receiver 11 of this portable terminal can receive the electric wave is reported to the GPS ground station 12. Accordingly, the GPS ground station 12 can find out a position of the portable terminal from a position of the satellite from which this electric wave can be received. This position information is used by the wireless telephony server apparatus.

In the above-mentioned embodiments, the wireless communication gateway server apparatus and the wireless telephony server apparatus are connected to each other through the Internet. However, a private line may be used in order to make the secret degree higher.

The above-mentioned embodiments do not depend on a particular wireless communication protocol. Thus, at a time of an internationally mutual connection including a foreign country, if it is possible to exchange a position information or it is possible to exchange a transmission reception type for the various parameters of the buffer memory emulator and the terminal kind report, the application does not need to be limited to a particular

territory.

Also, the similar effect can be attained even if the wireless communication gateway server apparatus also has the function of the wireless telephony server apparatus.

5 Moreover, in the above-mentioned embodiments, the access point is connected to specific one wireless communication gateway server apparatus. However, even if associated with the movement of the portable terminal, the access point automatically selects the nearest wireless
10 communication gateway server apparatus, it is possible to apply the process similar to that of the connection to the above-mentioned different wireless communication gateway server apparatus, and it is possible to attain the similar effect.

15 Advantageous Effects of the Invention

As can be evident from the above-mentioned explanations, in the mobile communication system, the method for reducing the connection time and the record medium for recording therein the program, the wireless
20 communication gateway server apparatus, if a congestion is induced in an access point that is used as a connection point to a wireless communication line and managed by the wireless communication gateway server apparatus, instructs the switching apparatus to carry out the
25 connection to another access point. Thus, even if the congestion is induced in the access point, it is possible to establish another access point in which the congestion

is not induced. Hence, it is possible to reduce the time necessary for the connection of the portable terminal.

The wireless communication gateway server apparatus holds therein the information with regard to the portable terminal connected to the access point managed by the wireless communication gateway server apparatus and the information, which is transferred by the information source server apparatus and stored in the memory, for the predetermined period even after the end of the communication with the portable terminal. When the congestion is induced in the managed access point, it compares the information with regard to the portable terminal, which is sent by the portable terminal connected to another access point, with the information with regard to the portable terminal previously connected to the access point to which it belongs. If their information coincide with each other, the information with regard to the portable terminal connected to the access point and the information stored in the memory are used to then resume the communication with the portable terminal. Thus, it is possible to reduce the time required when the portable terminal tries the process for carrying out the connection to the network. Hence, if the communication fee and the service based on the time are charged, it is possible to reduce the economic burden on the user.

The wireless communication gateway server apparatus transfers the information with regard to the portable

terminal connected to the access point managed by it to the wireless telephony server apparatus, and the wireless telephony server apparatus transfers the transferred information with regard to the portable terminal to the position information memory. Then, it is validated whether or not the position of the portable terminal is moved. If the portable terminal is moved, an address information on the network of the wireless communication gateway server apparatus connected before the movement is calculated from the position information. Thus, in the re-communication with the portable terminal whose the connection is once disconnected, the condition of the buffer memory can be prepared in advance in the wireless communication gateway server apparatus corresponding to the position to which the portable terminal is connected. Hence, it is possible to reduce the time in the connection processing time.

The wireless communication gateway server apparatus transfers the information with regard to the portable terminal connected to the access point managed it to the wireless telephony server apparatus, and the wireless telephony server apparatus transfers the information with regard to the portable terminal, which is reported by the portable terminal, to the position information memory, and it obtains the information with regard to the portable terminal, which is stored in the position information memory. The obtained information is compared with the

information with regard to the portable terminal, which is reported by the wireless communication gate, to then validate the legality of the portable terminal. Thus, it is possible to protect an illegal portable terminal from
5 accessing the network.

The wireless communication gateway server apparatus transfers the information with regard to the portable terminal connected to the access point managed by it to the wireless telephony server apparatus, and the wireless
10 telephony server apparatus transfers the transferred information with regard to the portable terminal to the position information memory. So, the accounting condition of the portable terminal can be checked by checking the accounting condition of the portable terminal
15 from the position information memory. When the access to the network is again tried, the accounting process can be continued.

The wireless communication gateway server apparatus grasps the histories of the information with regard to the
20 portable terminal that is connected to the wireless telephony server apparatus in the certain cycle and connected to the access point to which it belongs, and the position information of the portable terminal. Thus, it is possible to judge the terminal connected to the access
25 point under the control of the wireless communication gateway server apparatus.

The wireless communication gateway server apparatus

of the present invention instructs the switching apparatus, which carries out a connection to a line specified by a destination equipment number included in a call if a congestion is induced in the access point that is managed
5 by the wireless communication gateway server apparatus and used as a connection point to the wireless communication line, to carry out the connection to another access point, when a connection to an access point is requested by an equipment using the wireless communication line. Thus,
10 it is possible to establish another access point in which the congestion is not induced even if the congestion is induced in the access point. Hence, it is possible to reduce the time necessary for the connection to the network of the equipment using the wireless communication line.

15 The wireless communication gateway server apparatus holds therein information with regard to an equipment connected to the access point managed by the wireless communication gateway server apparatus and information transferred from an equipment existing on the network, for
20 a predetermined period even after the end of the communication with the equipment using the wireless communication line. Then, when a congestion is induced in the access point managed by it, it compares the information with regard to the equipment, which is sent
25 by the equipment using the wireless communication line and connected to another access point, with information with regard to an equipment using a wireless communication line

previously connected to the access point to which it belongs. If their information coincide with each other, the information with regard to the equipment connected to the access point and the stored information are used to
5 then resume the communication with the equipment using the wireless communication line. Thus, it is possible to reduce the time required when the equipment using the wireless communication line tries the process for carrying out the connection to the network. Hence, when the
10 communication fee and the service based on the time are charged, it is possible to reduce the economical burden on the user.

In the position information calculation system of the present invention, the wireless telephony server
15 apparatus transfers information with regard to an equipment using a wireless communication line to the position information memory. Then, it is validated whether or not a position of the equipment is moved. If it is moved, an address information of a managing device
20 for managing an access point to which the equipment using the wireless communication line is connected before the movement is calculated from the position information. For example, the calculated address information is transferred to the managing device for managing the access
25 point. Thus, in a re-communication with the equipment using the wireless communication line whose connection is once disconnected, the information with regard to the

equipment using the wireless communication line can be prepared in advance in the managing device corresponding to the position to which this equipment is connected. Hence, it is possible to reduce the connection processing
5 time.

The wireless telephony server apparatus transfers an identification information of the equipment that is included in the information with regard to the equipment that is reported by the equipment using the wireless
10 communication line, to the position information memory, and it obtains information with regard to the equipment that is stored in the position information memory. The obtained information is compared with information with regard to the equipment that is reported by a wireless
15 communication gate. The legality of the equipment using the wireless communication line can be validated to thereby prevent an illegal equipment from accessing the network.

What is claimed is:

1. A mobile wireless communication system comprising:
information source server apparatus storing
information;
a portable terminal carrying out a communication
5 with the information source server apparatus through a
wireless communication line and having a buffer memory
which stores the information transmitted from the
information source server apparatus;
a plurality of wireless communication gateway
10 server apparatuses, wherein a specific one of the
plurality of wireless communication gateway server
apparatuses which is determined based on an informed
position of the portable terminal, has a buffer memory
emulator which stores specification data which represents
15 a specification of the buffer memory and transmitters the
information from the information source server apparatus
to the portable terminal based on the specification data;
a switching apparatus setting a specific one
connection between the portable terminal and a specific
20 one wireless communication gateway server apparatus or
another connection between the portable terminal and
another wireless communication gateway server apparatus,
which is used when the communication between the portable
terminal and the specific one wireless communication
25 gateway server apparatus congests; and
a wireless telephony server apparatus informing

the position of the portable terminal to the plurality of wireless communication gateway server apparatuses.

2. A mobile wireless communication system as claimed in claim 1,

wherein the specific one wireless communication gateway server apparatus requests the switching apparatus
5 to change a connection from the specific one connection to the other connection based on the informed position.

3. A mobile wireless communication system as claimed in claim 1,

wherein the specific one wireless communication gateway server apparatus decides the other wireless
5 communication gateway server apparatus so that a new connecting destination of a connection between the one connection and the other connection is determined.

4. A mobile wireless communication system as claimed in claim 1,

wherein the specific one wireless communication gateway server apparatus informs to the other wireless
5 communication gateway server apparatus the specification data which is read from the buffer memory emulator, and

the other wireless communication gateway server apparatus stores the read specification data in the buffer memory emulator thereof and transfers the information from

- 10 the information source server apparatus to the portable terminal based on the read specification data.

5. A mobile wireless communication system as claimed in claim 1 comprising:

a network which is connected to the specific one wireless communication gateway server apparatus, the
5 another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus,

wherein the specific one wireless communication gateway server apparatus, the another wireless
10 communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the network.

6. A mobile wireless communication system as claimed in claim 1 comprising:

an internet network which is connected to the specific one wireless communication gateway server
5 apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus,

wherein the specific one wireless communication gateway server apparatus, the another wireless
10 communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus

communicate through the internet network.

7. A mobile wireless communication system as claimed in claim 1 comprising:

a satellite network which is connected to the specific one wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus,

wherein the specific one wireless communication gateway server apparatus, the another wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the satellite network.

8. A mobile wireless communication system comprising:
information source server apparatus stores information;

a portable terminal carrying out a communication with the information source server apparatus and having a buffer memory which stores the information transmitted from the information source server apparatus;

a wireless communication gateway server apparatus having a buffer memory emulator which stores specification data which represents a specification of the buffer memory and having a plurality of access points, specific one of which is determined based on an informed position of the

portable terminal, and transferring the information from the information source server apparatus to the portable
15 terminal based on the specification data;

a switching apparatus setting specific one connection between the portable terminal and specific one access point or another connection between the portable terminal and another access point, which is used when the
20 one access point congests; and

a wireless telephony server apparatus informing the position of the portable terminal to the wireless communication gateway server apparatus.

9. A mobile wireless communication system as claimed in claim 8,

wherein the wireless communication gateway server apparatus requests the switching apparatus to change a
5 connection from the specific one connection to the other connection based on the informed position.

10. A mobile wireless communication system as claimed in claim 8,

wherein the wireless communication gateway server apparatus refers the specification data in the buffer
5 memory emulator to access the portable terminal through the other access point.

11. A mobile wireless communication system as claimed

in claim 8 comprising:

a network which is connected to the wireless communication gateway server apparatus, the switching
 5 apparatus and the wireless telephony server apparatus,
 wherein the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the network.

12. A mobile wireless communication system as claimed in claim 8 comprising:

an internet network which is connected to the wireless communication gateway server apparatus, the
 5 switching apparatus and the wireless telephony server apparatus,

wherein the wireless communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the
 10 internet network.

13. A mobile wireless communication system as claimed in claim 8 comprising:

a satellite network which is connected to the wireless communication gateway server apparatus, the
 5 switching apparatus and the wireless telephony server apparatus,

wherein the wireless communication gateway server

apparatus, the switching apparatus and the wireless telephony server apparatus communicate through the
10 satellite network.

14. A method for mobile wireless communication system comprising:

storing a specification data which represents a specification of a buffer memory of a portable terminal
5 in a buffer memory emulator of specific one wireless communication gateway server apparatus when the portable terminal is connected to the specific one wireless communication gateway server apparatus;

changing specific one connection between the
10 portable terminal and the specific one wireless communication gateway server apparatus to another connection between the portable terminal and one of another wireless communication gateway server apparatus, which is used when the specific one wireless communication
15 gateway server apparatus has a congestion; and

transferring the specification data from the specific one wireless communication gateway server apparatus to the another wireless communication gateway server apparatus when the other connection is set.

15. A method for mobile wireless communication system as claimed in claim 14 comprising:

informing a position of the portable terminal from

a wireless telephony server apparatus to the specific one
5 wireless communication gateway server apparatus; and
requesting a change from a specific one connection
to the other connection to a switching apparatus which sets
a connection for the portable terminal based on the
informed position.

16. A method for mobile wireless communication system
as claimed in claim 14 comprising:

communicating of the specific one wireless
communication gateway server apparatus, another wireless
5 communication gateway server apparatus, the another the
switching apparatus and the wireless telephony server
apparatus through a network.

17. A method for mobile wireless communication system
as claimed in claim 14 comprising:

communicating of the specific one wireless
communication gateway server apparatus, another wireless
5 communication gateway server apparatus, the switching
apparatus and the wireless telephony server apparatus
through an internet network.

18. A method for mobile wireless communication system
as claimed in claim 14 comprising:

communicating of the specific one wireless
communication gateway server apparatus, another wireless

- 5 communication gateway server apparatus, the switching apparatus and the wireless telephony server apparatus through a satellite network.

19. A method for mobile wireless communication system comprising:

- changing specific one connection between the portable terminal and one access point of a wireless communication gateway server apparatus to another connection between the portable terminal and another access point of the wireless communication gateway server apparatus, which is used when the wireless communication gateway server apparatus has a congestion.

20. A method of mobile wireless communication system as claimed in claim 19 comprising:

- informing a position of the portable terminal from a wireless telephony server apparatus to the wireless communication gateway server apparatus; and

requesting a change from a specific one connection to the other connection to a switching apparatus which sets a connection for the portable terminal based on the informed position.

21. A method for mobile wireless communication system as claimed in claim 19 comprising:

communicating the wireless communication gateway

server apparatus, the switching apparatus and the wireless
5 telephony server apparatus communicate through a network.

22. A method for mobile wireless communication system
as claimed in claim 19 comprising:

communicating the wireless communication gateway
server apparatus, the switching apparatus and the wireless
5 telephony server apparatus communicate through an
internet network.

23. A method for mobile wireless communication system
as claimed in claim 19 comprising:

communicating the wireless communication gateway
server apparatus, the switching apparatus and the wireless
5 telephony server apparatus communicate through a
satellite network.

24. A wireless communication gateway server apparatus
comprising:

a buffer memory emulator storing a specification
data which represents a specification of a buffer memory
5 of a portable terminal,

wherein changing specific one connection with the
portable terminal to another connection between the
portable terminal and another wireless communication
gateway server apparatus, which is used when a congestion
10 of the specific one connection is happened; and

transferring the specification data in the buffer memory to the another wireless communication gateway server apparatus.

25. A wireless communication gateway server apparatus as claimed in claim 24,

wherein requesting to the switching apparatus which sets a connection for the portable terminal a change
5 from the specific one connection to the other connection based on a position data of the portable terminal.

26. A wireless communication gateway server apparatus as claimed in claim 24 comprising,

a plurality of access points, wherein a specific
10 one of the plurality of access points which is determined based on an informed position of the portable terminal,

wherein requesting to the switching apparatus which sets a connection for the portable terminal a change from a specific one connection of the specific one access
15 point to another connection of another access point based on the position of the portable terminal.

Abstract of the Disclosure

A mobile wireless communication system including information, a portable terminal, a plurality of wireless communication gateway server apparatus a switching
5 apparatus and a wireless telephony server apparatus. The information source server apparatus stores information. The portable terminal carries out a communication with the information source server apparatus through a wireless communication line and having a buffer memory which stores
10 the information from the information source server apparatus. The plurality of wireless communication gateway server apparatus has a buffer memory emulator which stores specification data. The specification data represents a specification of the buffer memory.
15 Furthermore, the plurality of wireless communication gateway server apparatus transmits the information to the portable terminal based on the specification data. The switching apparatus sets one connection between the portable terminal and specific one wireless communication
20 gateway server apparatus or another connection between the portable terminal and the other another wireless communication gateway server apparatus, which is used when the specific one wireless communication gateway server apparatus has a congestion. The wireless telephony
25 server apparatus informs a position of the portable terminal to the specific one wireless communication

gateway server apparatus.

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

Fig. 1 PRIOR ART




Fig. 2




Fig. 3

Tno	Sid	Cm
...		...

Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8





Fig. 9



Application for United States Patent

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name;

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

MOBILE WIRELESS COMMUNICATION SYSTEM CARRYING OUT COMMUNICATION OF A PORTABLE TERMINAL, AN INFORMATION SOURCE SERVER APPARATUS AND A WIRELESS COMMUNICATION GATEWAY SERVER APPARATUS

the specification of which:

(check one) ☒ is attached hereto

☐ was filed on _____, as
Application Serial No. _____
and was amended on _____.
(if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56*

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)			priority claimed	
<u>307805/1999</u>	<u>Japan</u>	<u>28/10/1999</u>	<u>X</u>	
(Number)	(Country)	(Day/Month/Year Filed)	yes	no
<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
(Number)	(Country)	(Day/Month/Year Filed)	yes	no
<u> </u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
(Number)	(Country)	(Day/Month/Year Filed)	yes	no

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, § 1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

(Application Serial No.)

(Filing Date)

(Status: patented, pending, abandoned)

Power of Attorney: As a named inventor, I hereby appoint Sean M. McGinn, Reg. 34,386, and Frederick W. Gibb, III, Reg. No. 37,629 as attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. All correspondence should be directed to McGinn & Gibb, P.C., 1701 Clarendon Boulevard, Suite 100, Arlington, Virginia 22209. Telephone calls should be directed to McGinn & Gibb, P.C. at (703) 294-6699.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful

false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full Name of Sole
or First Inventor HIDEHIRO MATSUMOTO
Inventor's Signature *Hidehiro Matsumoto* Date October 3, 2000
Residence Tokyo, Japan
Citizenship Japanese
Post Office Address c/o NEC Corporation, 7-1, Shiba 5-chome, Minato-ku, Tokyo, Japan

Full Name of Second
Joint Inventor, If Any _____
Inventor's Signature _____ Date _____
Residence _____
Citizenship _____
Post Office Address _____

Full Name of Third
Joint Inventor, If Any _____
Inventor's Signature _____ Date _____
Residence _____
Citizenship _____
Post Office Address _____

Full Name of Fourth
Joint Inventor, If Any _____
Inventor's Signature _____ Date _____
Residence _____
Citizenship _____
Post Office Address _____

(An additional sheet(s) is/are attached hereto if the present invention includes more than four inventors.)

*Title 37, Code of Federal Regulations, § 1.56:

(a) A patent by its very nature is affected with a public interest. The public interest is best served, and the most effective patent examination occurs when, at the time an application is being examined, the Office is aware of and evaluates the teachings of all information material to patentability. Each individual associated with the filing and prosecution of a patent application has a duty of candor and good faith toward the Patent and Trademark Office, which includes a duty to disclose to the Office all information known to that individual to be material to patentability as defined in this section. The duty to disclose information exists with respect to each pending claim until the claim is canceled or withdrawn from consideration, or the application becomes abandoned.

(b) Under this section, information is material to patentability when it is not cumulative to information already of record or being made of record in the application, and (1) it establishes, by itself or in combination with other information, a prima facie case of unpatentability; or (2) it refutes, or is inconsistent with, a position the applicant takes in: (i) opposing an argument of unpatentability relied on by the Office, or (ii) asserting an argument of patentability.